

## ABLOY® HIGH SECURITY RIM LOCKS



ABLOY® RIM LOCKS employ the unique ABLOY® detainer disc cylinder technology that provides superior master-keying possibilities and enable keying of different product types in single master-key-system.

# ABLOY® RIM LOCK CASES

The functions of the new lock cases are the same as in earlier versions. Bolt deadlocks automatically when door is closed. Bolt throw 20 mm. Bolt can be latched by depressing it into the lock case. Bolt is released by depressing it further and turning thumbturn simultaneously. **The new lock cases are available only with brushed black nickel finish. Thumbturn only in bright chrome.**

## LOCK CASE ABLOY®RI211

General rim lock case which is used on house doors and apartment doors, storeroom doors etc.

Also available

## LOCK CASE ABLOY®RI212

Lock case for twin cylinder outside. Bolt 14 mm.

## LOCK CASE ABLOY®RI213

Lock case for fire doors (max. 60 minutes). Bolt 14 mm.

## MATERIALS

Lock case and thumbturn of zinc. Bolt of brass.



Available with key systems

**ABLOY® PROTEC (CY053N, CY054N)**

**ABLOY® NOVEL (CY053U, CY054U)**

**ABLOY® CLASSIC (5190C, CY054C)**

## MATERIALS

Cylinders CY053 and 5190C of brass. Cylinder CY054 of case hardened steel.

## KEEPS



RI410 RI411

For inward opening doors.  
Materials:  
Body of steel and case of zinc.

## STRIKER PLATES



RI401 RI402

For outward opening doors.  
Material: steel



[www.abloy.com](http://www.abloy.com)

Abloy Oy  
Wahlforsinkatu 20  
P.O. Box 108  
FI-80101 JOENSUU  
FINLAND  
Tel. +358 20 599 2501  
Fax +358 20 599 2209

